

Configured Settings

CCD Information

Customer Name: EMERSON
 CCD Name: EMERSON_2759815
 Account Number: 2759815
 Model/Solution: ALL MFP DEVICES
 CCD Type: Hardware
 CCD Number: 5209

Manual Settings

Full Path	Value	Comments
Device Settings --> Email --> Email --> Administrator Email Address	PrinterName@Emerson.com	Manual Configuration Needed
Device Settings --> Email --> SMTP --> SMTP Port No	25	Manual Configuration Needed
Device Settings --> Email --> SMTP --> SMTP Server Name	inetmail.emrsn.net	Manual Configuration Needed
Device Settings --> Paper --> Tray 1 --> Basis Weight	Plain Paper 1 (60 to 74g/m ²)	Manual Configuration Needed
Device Settings --> Program/Change Administrator --> Administrator 1 --> Login User Name	Admin	Manual Configuration Needed
Device Settings --> Program/Change Administrator --> Machine Administrator --> Administrator 1	true	Manual Configuration Needed
Device Settings --> Program/Change Administrator --> User Administrator --> Administrator 1	true	Manual Configuration Needed
Device Settings --> Program/Change Administrator --> User Administrator --> Administrator 2	true	Manual Configuration Needed
Device Settings --> System --> General Settings --> Display IP Address on Device Display Panel	Inactive	Manual Configuration Needed
Device Settings --> System --> General Settings --> Media Slot Use - Print from Memory Storage Device	Prohibit	Manual Configuration Needed

Device Settings --> System --> General Settings --> Media Slot Use - Store to Memory Device	Prohibit	Manual Configuration Needed
Device Settings --> System --> Paper Tray Priority --> Copier	Tray 1	Manual Configuration Needed
Device Settings --> System --> Paper Tray Priority --> Fax	Tray 1	Manual Configuration Needed
Device Settings --> User Authentication Mgmt --> User Authentication Management --> User Authentication Management	Off	Manual Configuration Needed
Manual Configuration --> General Configuration --> Dynamic settings --> AFTER SP5305 UPDATED - SET SLEEP MODE TIMER - 240 MIN	AFTER SP5305 UPDATED - SET SLEEP MODE TIMER - 240 MIN	Manual Configuration Needed
Manual Configuration --> General Configuration --> Dynamic settings --> CARD READER	Plug Card Reader into the Operation Panel; Field to install PCC V5 and this requires the Card Reader to be plugged into the Operation Panel.	Manual Configuration Needed
Manual Configuration --> General Configuration --> Dynamic settings --> Emerson Custom EID Label	Please add Emerson Custom EID Label during shop setup (I020-6347-V02 - see picture attached	Manual Configuration Needed
Manual Configuration --> General Configuration --> Dynamic settings --> Emerson Custom EID Label - Ordering More (Steps)	Each warehouse would need to send a request by email to the EID Tag Requests group mailbox (RUS-EID Tag Requests <EIDTagRequests@ricoh-usa.com>) and cc - Jay.takashima@ricoh-usa.com You would need to provide the EID tag version for Emerson so that they print and send you the correct tag. Emerson I020-6347-V02 Info needed below in the request. • Requestor Name: • Requestor Phone Number: • Quantity Needed: • Attention: • Address • UPS Shipper Code • Identify Ground or Overnight method	Manual Configuration Needed
Manual Configuration --> General Configuration --> Dynamic settings --> Remote Panel Operation	ENABLE	Manual Configuration Needed
Manual Configuration --> General Configuration --> Dynamic settings --> SET USB DEVICE TO ALWAYS ACTIVE	SP5191-001 set to 0; SP5305 set to 0 Control Panel Service mode>Settings>USB Device>Device Always Active	Manual Configuration Needed

Manual Configuration --> General Configuration --> Dynamic settings --> SP 5191-001 set to 0	SP 5191-001 set to 0	Manual Configuration Needed
Manual Configuration --> General Configuration --> Dynamic settings --> SP5305 - SET TO 0 & UPDATE SLEEP TIMER 240 MIN	SP 5305 - Set to 0	Manual Configuration Needed
Manual Configuration --> General Configuration --> Dynamic settings --> Update Card Reader to allow it to beep with card authentication Kofax Reader Maintainer _2_12_00	Update Card Reader to allow it to beep with card authentication Kofax Reader Maintainer _2_12_00	Manual Configuration Needed
Manual Configuration --> General Configuration --> Field setup --> Field Work Instructions	Emerson Logo - Please add to panel	Manual Configuration Needed
Manual Configuration --> General Configuration --> General Configuration Text - -> Configuration Instructions	Emerson Logo - Please add	Manual Configuration Needed
Scanner --> Default Settings for Simplified Screens (Classic) on Device --> Send File Type --> Send File Type	Single Page: PDF	Manual Configuration Needed
Scanner --> General Settings --> Print & Delete Scanner Journal --> Print & delete scanner journal	Print and Delete All	Manual Configuration Needed
Scanner --> Send Settings --> Compression (Black & White) --> Compression (black & white) Status	MMR	Manual Configuration Needed
Scanner --> Send Settings --> Compression Method for High Compression PDF --> Compression Method for Text	MMR	Manual Configuration Needed
Scanner --> Send Settings --> Divide & Send Email --> Enable divide & send email	Yes (per Max. Size)	Manual Configuration Needed
Scanner --> Send Settings --> File Emailing Method --> File emailing method	Attach to Email	Manual Configuration Needed
Scanner --> Send Settings --> Max Email Size --> Set max email size	Off	Manual Configuration Needed
Scanner --> Send Settings --> Max Email Size --> Set max email size --> Max email size	102400	Manual Configuration Needed
SOP --> Wireless & Networks --> Interface Settings --> Interface settings	Machine Network	Manual Configuration Needed
User Tools --> Administrator Tools --> General Settings --> HDD Erase Method	DoD (5220.22-M)	Manual Configuration Needed

Automatic Settings

--	--	--

Full Path	Value	Comments
-----------	-------	----------