

Configured Settings

CCD Information

Customer Name: International Flavors & Fragrances Inc. CCD Name: International Flavors & amp; Fragrances Inc._2070433 Account Number: 2070433 **Model/Solution: IMC3010** CCD Type: Hardware CCD Number: 12447

Manual Settings

Full Path	Value	Comments
Device Settings> Administrator Authentication Management> File Administrator Authentication> File Administrator Authentication	On	
Device Settings> Administrator Authentication Management> Machine Administrator Authentication> Machine Administrator Authentication	On	
Device Settings> Administrator Authentication Management> Network Administrator Authentication> Network Administrator Authentication	On	
Device Settings> Administrator Authentication Management> User Administrator Authentication> User Administrator Authentication	On	
Device Settings> Email> Email> Administrator Email Address	gps-device@iff.com	
Device Settings> Email> Email> Administrator Email Address	gps-device@iff.com	
Device Settings> Email> Email> Auto Specify Sender Name	On	
Device Settings> Email> Reception> Max Reception Email Size	2	
Device Settings> Email> SMTP> SMTP Server Name	smtp.global.iff.com	

Device Settings> Program/Change Administrator> Administrator 1> Login User Name	admin
Device Settings> Program/Change Administrator> Administrator 1> Login User Password	20r1c0h21
Device Settings> Program/Change Administrator> Administrator 2> Login User Name	ricoh
Device Settings> Program/Change Administrator> Administrator 2> Login User Password	21!ffxx1
Device Settings> Program/Change Administrator> File Administrator> Administrator 1	true
Device Settings> Program/Change Administrator> Machine Administrator> Administrator 1	true
Device Settings> Program/Change Administrator> Network Administrator> Administrator 1	true
Device Settings> Program/Change Administrator> User Administrator> Administrator 1	true
Device Settings> Program/Change Administrator> User Administrator> Administrator 2	true
Device Settings> System> General Settings> Media Slot Use - Print from Memory Storage Device	Prohibit
Device Settings> System> General Settings> Media Slot Use - Store to Memory Device	Prohibit
Manual Configuration> General Configuration> Dynamic settings> Device Certificate	Validity Period 10 years Algorithm Signature Max key length supported by device (512/1024/2048/4096)
Manual Configuration> General Configuration> Dynamic settings> Device Certificate	Validity Period 10 years Algorithm Signature Max key length supported by device (512/1024/2048/4096)
Manual Configuration> General Configuration> Dynamic settings> HDD enabled devices *****NOTE****	must enable encryption and DOSS - set to overwrite method DoD for all devices configured with HDD

Manual Configuration> General Configuration> Dynamic settings> HDD enabled devices *****NOTE****	must enable encryption and DOSS - set to overwrite method DoD for all devices configured with HDD
Manual Configuration> General Configuration> Dynamic settings> SP Modes: Copy SP Modes	SP 5-966-001 set to 1
Manual Configuration> General Configuration> Dynamic settings> SP Modes: Copy SP Modes	SP 5-966-001 set to 1
Network Settings> Airprint> AirPrint> AirPrint	Inactive
Network Settings> Airprint> AirPrint> AirPrint	Inactive
Network Settings> Bonjour> Bonjour> IPV4	Inactive
Network Settings> Community> Community Name 1> Community name	20iFF%GpS21
Network Settings> Community> Community Name 1> IPv4	Active
Network Settings> Community> Community Name 2> Access Type	read-write
Network Settings> Community> Community Name 2> Community name	r1c0h#pCFS
Network Settings> Community> Community Name 2> IPv4	Active
Network Settings> IPV4> Details> DIPRINT Timeout Period	60
Network Settings> IPV4> Details> DNS Server	Specify
Network Settings> IPV4> Details> DNS Server> DNS Server 1	10.13.140.12
Network Settings> IPV4> Details> DNS Server> DNS Server 2	10.13.140.10
Network Settings> IPV4> Details> DNS Server> DNS Server 3	0.0.0.0
Network Settings> IPV4> Details> FTP	Inactive
Network Settings> IPV4> Details> IPP	Active
Network Settings> IPV4> Details>	Active

10/18/2023

Network Settings> IPV4> Details> RSH/RCP	Active
Network Settings> IPV4> Details> SFTP	Active
Network Settings> IPV4> Details> WSD (Device)	Active
Network Settings> IPV4> Details> WSD (Printer)	Active
Network Settings> IPV4> Ethernet> DHCP	Inactive
Network Settings> IPV4> Ethernet> Domain Name	Specify
Network Settings> IPV4> Ethernet> Domain Name> Domain Name	global.iff.com
Network Settings> IPV4> Ethernet> Primary WINS Server	000.000.000
Network Settings> IPV4> Ethernet> Secondary WINS Server	000.000.000
Network Settings> IPV4> Ethernet> WINS	Deactive
Network Settings> IPV6> IPV6> IPV6	Inactive
Network Settings> SNMP> Protocol> IPv4	Active
Network Settings> SNMP> SNMP> SNMP	Active
Network Settings> SNMPv3> Protocol> SNMP	Active
Network Settings> SNMPv3> Protocol> SNMP	Active
Network Settings> SNMPv3> SNMP> IPv4	Active
Network Settings> SNMPv3> SNMPv3 Setting> Authentication Algorithm	MD5
Network Settings> SNMPv3> SNMPv3 Setting> Encryption Algorithm	DES
Network Settings> SNMPv3> SNMPv3 Setting> Permit SNMPv3 Communication	Encryption/Cleartext
Network Settings> SNMPv3> SNMPv3 Setting> SNMPv3 Function	Active
Network Settings> SNMPv3> SNMPv3 Setting> SNMPv3 Trap Communication	Active

10/18/2023

Printer Settings> Printer Basic Settings> System> Auto Continue	On
Printer Settings> Printer Basic Settings> System> Auto Continue> Auto Continue Time	5
Printer Settings> Printer Basic Settings> System> Auto Delete Store Print Jobs	On
Printer Settings> Printer Basic Settings> System> Auto Delete Store Print Jobs> Time(days)	1
Printer Settings> Printer Basic Settings> System> Auto Delete Temporary Print Jobs	On
Printer Settings> Printer Basic Settings> System> Auto Delete Temporary Print Jobs > Time(days)	3
Remote> Remote Communications> @Remote Registration> Registration Options	DO NOT REGISTER: SNLX with @Remote Connector/ @Remote Connector NX
Remote> Remote Communications> @Remote Registration> Registration Options	DO NOT REGISTER: SNLX with @Remote Connector/ @Remote Connector NX
Scanner> Default Settings for Normal Screens (Classic) on Device> Send File Type> Send File Type	Multi-page: PDF
Scanner> Default Settings for Normal Screens (Classic) on Device> Send File Type> Send File Type	Multi-page: PDF
Scanner> Default Settings for Simplified Screens (Classic) on Device> Send File Type> Send File Type	Multi-page: PDF
Scanner> Default Settings for Simplified Screens (Classic) on Device> Send File Type> Send File Type	Multi-page: PDF
Scanner> Send Settings> Insert Additional Email Info> Insert Additional Email Info	On
Scanner> Send Settings> Insert Additional Email Info> Insert Additional Email Info> Language	English
Scanner> Send Settings> Max Email Size > Set max email size	On
Scanner> Send Settings> Max Email Size > Set max email size> Max email size	35000

Security> IEEE 802.1X> Domain Name > Domain Name	global.iff.com
Security> Network> Bonjour> IPV4	Inactive
Security> Network> DIPRINT> IPV4	Active
Security> Network> FTP> IPV6	Inactive
Security> Network> LPR> IPV4	Active
Security> Network> NetBIOS over TCP/IPV4> IPV4	Inactive
Security> Network> RHPP> IPV4	Active
Security> Network> RSH/RCP> IPV4	Active
Security> Network> sftp> IPV4	Inactive
Security> Network> SNMP> Permit Settings by SNMPv1 and SNMPv2	On
Security> Network> SNMP> SNMPv1, v2 Function	Active
Security> Network> SNMP> SNMPv3	Active
Security> Network> SSDP> IPV4	Inactive
Security> Network> SSDP> IPV4	Inactive
Security> Network> ssh> IPV4	Inactive
Security> Network> TCP/IP> IPV4	Active
Security> Network> TELNET> IPV4	Active
Security> Network> WSD (Device)> IPV4	Active
Security> Network> WSD (Device)> IPV4	Active
Security> Network> WSD (Encrypted Communication of Device)> IPV4	Active
Security> Network> WSD (Printer)> IPV4	Active
Security> Network> WSD (Scanner)> IPV4	Active
SOP> DEVICE> Remote Panel Operation > Remote Panel Operation - Manual	Enabled
SOP> DEVICE> Remote Panel Operation > Remote Panel Operation - Manual	Enabled
SOP> PERSONAL> Screen Device Settings> Screen SD Card Slot	Inactive

SOP> PERSONAL> Screen Device Settings> Screen USB Memory Slot	Inactive
SP Settings> Copy SP Modes> SP5 - 888 > 888 - Personal info protect	1: Protection for logs
SP Settings> Copy SP Modes> SP5 - 888 > 888 - Personal info protect	1: Protection for logs
SP Settings> Copy SP Modes> SP5 - 967 - 001> 5-967-001 – Disable Document Server	1: OFF
SP Settings> Copy SP Modes> SP5 - 967 - 001> 5-967-001 – Disable Document Server	1: OFF
SP Settings> Printer SP Modes> SP1-001 > 1001-006 bit 1 - Lock Sample print	1: ON
SP Settings> Printer SP Modes> SP1-001 > 1001-006 bit 1 - Lock Sample print	1: ON
User Tools> Administrator Authentication Management> File Administrator Authentication> File Administrator Authentication	On
User Tools> Administrator Authentication Management> User Administrator Authentication> User Administrator Authentication	On
User Tools> Administrator Tools> General Settings> Auto erase memory setting	On
User Tools> Administrator Tools> General Settings> HDD Erase Method	DoD (5220.22-M)
User Tools> Administrator Tools> General Settings> Machine Data Encryption Settings/Encrypt	Format All Data
User Tools> Administrator Tools> General Settings> Machine Data Encryption Settings/Encrypt	Format All Data
User Tools> File Transfer> General Settings> Administrators email address	gps-device@iff.com
User Tools> File Transfer> General Settings> Administrators email address	gps-device@iff.com
User Tools> File Transfer> General Settings> Max reception email size	35
User Tools> File Transfer> SMTP> SMTP Server Name	smtp.global.iff.com

Automatic Settings

Full Path	Value	Comments
Device Settings> Administrator Authentication Management> File Administrator Authentication> File Administrator Authentication	On	
Device Settings> Administrator Authentication Management> File Administrator Authentication> File Administrator Authentication> Administrator Tools	true	
Device Settings> Administrator Authentication Management> Machine Administrator Authentication> Machine Administrator Authentication	On	
Device Settings> Administrator Authentication Management> Machine Administrator Authentication> Machine Administrator Authentication> Administrator Tools	true	
Device Settings> Administrator Authentication Management> Machine Administrator Authentication> Machine Administrator Authentication> File Transfer	true	
Device Settings> Administrator Authentication Management> Machine Administrator Authentication> Machine Administrator Authentication> General Features	true	
Device Settings> Administrator Authentication Management> Machine Administrator Authentication> Machine Administrator Authentication> Interface	true	
Device Settings> Administrator Authentication Management> Machine Administrator Authentication> Machine Administrator Authentication> Maintenance	true	
Device Settings> Administrator Authentication Management> Machine Administrator Authentication> Machine Administrator Authentication> Timer Settings	true	

Device Settings> Administrator Authentication Management> Machine Administrator Authentication> Machine Administrator Authentication> Tray Paper Settings	true
Device Settings> Administrator Authentication Management> Network Administrator Authentication> Network Administrator Authentication	On
Device Settings> Administrator Authentication Management> Network Administrator Authentication> Network Administrator Authentication> Administrator Tools	true
Device Settings> Administrator Authentication Management> Network Administrator Authentication> Network Administrator Authentication> File Transfer	true
Device Settings> Administrator Authentication Management> Network Administrator Authentication> Network Administrator Authentication> Interface	true
Device Settings> Administrator Authentication Management> User Administrator Authentication> User Administrator Authentication	On
Device Settings> Administrator Authentication Management> User Administrator Authentication> User Administrator Authentication> Administrator Tools	true
Device Settings> Email> Email> Auto Specify Sender Name	On
Device Settings> Email> Reception> Max Reception Email Size	2
Device Settings> Email> SMTP> SMTP Server Name	smtp.global.iff.com
Device Settings> Program/Change Administrator> Administrator 1> Login User Name	admin
Device Settings> Program/Change Administrator> Administrator 1> Login User Password	20r1c0h21
Device Settings> Program/Change Administrator> Administrator 2> Login User Name	ricoh

Device Settings> Program/Change Administrator> Administrator 2> Login User Password	21!ffxx1
Device Settings> Program/Change Administrator> File Administrator> Administrator 1	true
Device Settings> Program/Change Administrator> Machine Administrator> Administrator 1	true
Device Settings> Program/Change Administrator> Network Administrator> Administrator 1	true
Device Settings> Program/Change Administrator> User Administrator> Administrator 1	true
Device Settings> Program/Change Administrator> User Administrator> Administrator 2	true
Device Settings> System> General Settings> Media Slot Use - Print from Memory Storage Device	Prohibit
Device Settings> System> General Settings> Media Slot Use - Store to Memory Device	Prohibit
Network Settings> Bonjour> Bonjour> IPV4	Inactive
Network Settings> Community> Community Name 1> Community name	20iFF%GpS21
Network Settings> Community> Community Name 1> IPv4	Active
Network Settings> Community> Community Name 2> Access Type	read-write
Network Settings> Community> Community Name 2> Community name	r1c0h#pCFS
Network Settings> Community> Community Name 2> IPv4	Active
Network Settings> IPV4> Details> DIPRINT Timeout Period	60
Network Settings> IPV4> Details> DNS Server	Specify
Network Settings> IPV4> Details> DNS Server> DNS Server 1	10.13.140.12

Network Settings> IPV4> Details> DNS Server> DNS Server 2	10.13.140.10
Network Settings> IPV4> Details> DNS Server> DNS Server 3	0.0.0.0
Network Settings> IPV4> Details> FTP	Inactive
Network Settings> IPV4> Details> IPP	Active
Network Settings> IPV4> Details> RHPP	Active
Network Settings> IPV4> Details> RSH/RCP	Active
Network Settings> IPV4> Details> SFTP	Active
Network Settings> IPV4> Details> WSD (Device)	Active
Network Settings> IPV4> Details> WSD (Printer)	Active
Network Settings> IPV4> Ethernet> DHCP	Inactive
Network Settings> IPV4> Ethernet> Domain Name	Specify
Network Settings> IPV4> Ethernet> Domain Name> Domain Name	global.iff.com
Network Settings> IPV4> Ethernet> Primary WINS Server	000.000.000
Network Settings> IPV4> Ethernet> Secondary WINS Server	000.000.000
Network Settings> IPV4> Ethernet> WINS	Deactive
Network Settings> IPV6> IPV6> IPV6	Inactive
Network Settings> SNMP> Protocol> IPv4	Active
Network Settings> SNMP> SNMP> SNMP	Active
Network Settings> SNMPv3> SNMP> IPv4	Active
Network Settings> SNMPv3> SNMPv3 Setting> Authentication Algorithm	MD5
Network Settings> SNMPv3> SNMPv3 Setting> Encryption Algorithm	DES

Network Settings> SNMPv3> SNMPv3 Setting> Permit SNMPv3 Communication	Encryption/Cleartext
Network Settings> SNMPv3> SNMPv3 Setting> SNMPv3 Function	Active
Network Settings> SNMPv3> SNMPv3 Setting> SNMPv3 Trap Communication	Active
Printer Settings> Printer Basic Settings> System> Auto Continue	On
Printer Settings> Printer Basic Settings> System> Auto Continue> Auto Continue Time	5
Printer Settings> Printer Basic Settings> System> Auto Delete Store Print Jobs	On
Printer Settings> Printer Basic Settings> System> Auto Delete Store Print Jobs> Time(days)	1
Printer Settings> Printer Basic Settings> System> Auto Delete Temporary Print Jobs	On
Printer Settings> Printer Basic Settings> System> Auto Delete Temporary Print Jobs > Time(days)	3
Scanner> Send Settings> Insert Additional Email Info> Insert Additional Email Info	On
Scanner> Send Settings> Insert Additional Email Info> Insert Additional Email Info> Language	English
Scanner> Send Settings> Max Email Size > Set max email size	On
Scanner> Send Settings> Max Email Size > Set max email size> Max email size	35000
Security> IEEE 802.1X> Domain Name > Domain Name	global.iff.com
Security> Network> Bonjour> IPV4	Inactive
Security> Network> DIPRINT> IPV4	Active
Security> Network> FTP> IPV6	Inactive
Security> Network> LPR> IPV4	Active
Security> Network> NetBIOS over TCP/IPV4> IPV4	Inactive
Security> Network> RHPP> IPV4	Active
Security> Network> RSH/RCP> IPV4	Active

Security> Network> sftp> IPV4	Inactive
Security> Network> SNMP> Permit Settings by SNMPv1 and SNMPv2	On
Security> Network> SNMP> SNMPv1, v2 Function	Active
Security> Network> SNMP> SNMPv3	Active
Security> Network> ssh> IPV4	Inactive
Security> Network> TCP/IP> IPV4	Active
Security> Network> TELNET> IPV4	Active
Security> Network> WSD (Encrypted Communication of Device)> IPV4	Active
Security> Network> WSD (Printer)> IPV4	Active
Security> Network> WSD (Scanner)> IPV4	Active
SOP> PERSONAL> Screen Device Settings> Screen SD Card Slot	Inactive
SOP> PERSONAL> Screen Device Settings> Screen USB Memory Slot	Inactive
User Tools> Administrator Authentication Management> File Administrator Authentication> File Administrator Authentication	On
User Tools> Administrator Authentication Management> File Administrator Authentication> File Administrator Authentication> Administrator Tools	true
User Tools> Administrator Authentication Management> User Administrator Authentication> User Administrator Authentication	On
User Tools> Administrator Authentication Management> User Administrator Authentication> User Administrator Authentication> Administrator Tools	true
User Tools> Administrator Tools> General Settings> Auto erase memory setting	On
User Tools> Administrator Tools> General Settings> HDD Erase Method	DoD (5220.22-M)
User Tools> File Transfer> General Settings> Max reception email size	35