

# Configured Settings

## CCD Information

Customer Name: International Flavors & Fragrances Inc.  
 CCD Name: International Flavors & Fragrances Inc.\_2070433  
 Account Number: 2070433  
**Model/Solution: IMC2510**  
 CCD Type: Hardware  
 CCD Number: 12446

## Manual Settings

| Full Path                                                                                                     | Value                                                                                                | Comments |
|---------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|----------|
| Device Settings --> Email --> Email --> Administrator Email Address                                           | gps-device@iff.com                                                                                   |          |
| Manual Configuration --> General Configuration --> Dynamic settings --> Device Certificate                    | Validity Period 10 years Algorithm Signature Max key length supported by device (512/1024/2048/4096) |          |
| Manual Configuration --> General Configuration --> Dynamic settings --> HDD enabled devices *****NOTE*****    | must enable encryption and DOSS - set to overwrite method DoD for all devices configured with HDD    |          |
| Manual Configuration --> General Configuration --> Dynamic settings --> SP Modes: Copy SP Modes               | SP 5-966-001 set to 1                                                                                |          |
| Network Settings --> Airprint --> AirPrint --> AirPrint                                                       | Inactive                                                                                             |          |
| Network Settings --> SNMPv3 --> Protocol --> SNMP                                                             | Active                                                                                               |          |
| Remote --> Remote Communications --> @Remote Registration --> Registration Options                            | DO NOT REGISTER: SNLX with @Remote Connector/ @Remote Connector NX                                   |          |
| Scanner --> Default Settings for Normal Screens (Classic) on Device --> Send File Type --> Send File Type     | Multi-page: PDF                                                                                      |          |
| Scanner --> Default Settings for Simplified Screens (Classic) on Device --> Send File Type --> Send File Type | Multi-page: PDF                                                                                      |          |
| Security --> Network --> SSDP --> IPV4                                                                        | Inactive                                                                                             |          |

|                                                                                                      |                        |
|------------------------------------------------------------------------------------------------------|------------------------|
| Security --> Network --> WSD (Device) --> IPV4                                                       | Active                 |
| SOP --> DEVICE --> Remote Panel Operation --> Remote Panel Operation - Manual                        | Enabled                |
| SP Settings --> Copy SP Modes --> SP5 - 888 --> 888 - Personal info protect                          | 1: Protection for logs |
| SP Settings --> Copy SP Modes --> SP5 - 967 - 001 --> 5-967-001 – Disable Document Server            | 1: OFF                 |
| SP Settings --> Printer SP Modes --> SP1-001 --> 1001-006 bit 1 - Lock Sample print                  | 1: ON                  |
| User Tools --> Administrator Tools --> General Settings --> Machine Data Encryption Settings/Encrypt | Format All Data        |
| User Tools --> File Transfer --> General Settings --> Administrators email address                   | gps-device@iff.com     |
| User Tools --> File Transfer --> SMTP --> SMTP Server Name                                           | smtp.global.iff.com    |

## Automatic Settings

| Full Path                                                                                                                                                             | Value | Comments |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|----------|
| Device Settings --> Administrator Authentication Management --> File Administrator Authentication --> File Administrator Authentication                               | On    |          |
| Device Settings --> Administrator Authentication Management --> File Administrator Authentication --> File Administrator Authentication --> Administrator Tools       | true  |          |
| Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication                         | On    |          |
| Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication --> Administrator Tools | true  |          |
| Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication --> File Transfer       | true  |          |

Device Settings --> Administrator  
Authentication Management --> Machine  
Administrator Authentication --> Machine  
Administrator Authentication --> General  
Features

true

Device Settings --> Administrator  
Authentication Management --> Machine  
Administrator Authentication --> Machine  
Administrator Authentication --> Interface

true

Device Settings --> Administrator  
Authentication Management --> Machine  
Administrator Authentication --> Machine  
Administrator Authentication --> Maintenance

true

Device Settings --> Administrator  
Authentication Management --> Machine  
Administrator Authentication --> Machine  
Administrator Authentication --> Timer  
Settings

true

Device Settings --> Administrator  
Authentication Management --> Machine  
Administrator Authentication --> Machine  
Administrator Authentication --> Tray Paper  
Settings

true

Device Settings --> Administrator  
Authentication Management --> Network  
Administrator Authentication --> Network  
Administrator Authentication

On

Device Settings --> Administrator  
Authentication Management --> Network  
Administrator Authentication --> Network  
Administrator Authentication --> Administrator  
Tools

true

Device Settings --> Administrator  
Authentication Management --> Network  
Administrator Authentication --> Network  
Administrator Authentication --> File Transfer

true

Device Settings --> Administrator  
Authentication Management --> Network  
Administrator Authentication --> Network  
Administrator Authentication --> Interface

true

Device Settings --> Administrator  
Authentication Management --> User  
Administrator Authentication --> User  
Administrator Authentication

On

Device Settings --> Administrator  
Authentication Management --> User  
Administrator Authentication --> User  
Administrator Authentication --> Administrator  
Tools

true

Device Settings --> Email --> Email --> Auto Specify Sender Name On

Device Settings --> Email --> Reception --> Max Reception Email Size 2

Device Settings --> Email --> SMTP --> SMTP Server Name smtp.global.iff.com

Device Settings --> Program/Change Administrator --> Administrator 1 --> Login User Name admin

Device Settings --> Program/Change Administrator --> Administrator 1 --> Login User Password 20r1c0h21

Device Settings --> Program/Change Administrator --> Administrator 2 --> Login User Name ricoh

Device Settings --> Program/Change Administrator --> Administrator 2 --> Login User Password 21!ffxx1

Device Settings --> Program/Change Administrator --> File Administrator --> Administrator 1 true

Device Settings --> Program/Change Administrator --> Machine Administrator --> Administrator 1 true

Device Settings --> Program/Change Administrator --> Network Administrator --> Administrator 1 true

Device Settings --> Program/Change Administrator --> User Administrator --> Administrator 1 true

Device Settings --> Program/Change Administrator --> User Administrator --> Administrator 2 true

Device Settings --> System --> General Settings --> Media Slot Use - Print from Memory Storage Device Prohibit

Device Settings --> System --> General Settings --> Media Slot Use - Store to Memory Device Prohibit

Network Settings --> Bonjour --> Bonjour --> IPV4 Inactive

Network Settings --> Community --> Community Name 1 --> Community name 20iFF%GpS21

|                                                                           |                 |
|---------------------------------------------------------------------------|-----------------|
| Network Settings --> Community --><br>Community Name 1 --> IPv4           | Active          |
| Network Settings --> Community --><br>Community Name 2 --> Access Type    | read-write      |
| Network Settings --> Community --><br>Community Name 2 --> Community name | r1c0h#pCFS      |
| Network Settings --> Community --><br>Community Name 2 --> IPv4           | Active          |
| Network Settings --> IPV4 --> Details --><br>DIPRINT Timeout Period       | 60              |
| Network Settings --> IPV4 --> Details --> DNS<br>Server                   | Specify         |
| Network Settings --> IPV4 --> Details --> DNS<br>Server --> DNS Server 1  | 10.13.140.12    |
| Network Settings --> IPV4 --> Details --> DNS<br>Server --> DNS Server 2  | 10.13.140.10    |
| Network Settings --> IPV4 --> Details --> DNS<br>Server --> DNS Server 3  | 0.0.0.0         |
| Network Settings --> IPV4 --> Details --> FTP                             | Inactive        |
| Network Settings --> IPV4 --> Details --> IPP                             | Active          |
| Network Settings --> IPV4 --> Details --><br>RHPP                         | Active          |
| Network Settings --> IPV4 --> Details --><br>RSH/RCP                      | Active          |
| Network Settings --> IPV4 --> Details --><br>SFTP                         | Active          |
| Network Settings --> IPV4 --> Details --> WSD<br>(Device)                 | Active          |
| Network Settings --> IPV4 --> Details --> WSD<br>(Printer)                | Active          |
| Network Settings --> IPV4 --> Ethernet --><br>DHCP                        | Inactive        |
| Network Settings --> IPV4 --> Ethernet --><br>Domain Name                 | Specify         |
| Network Settings --> IPV4 --> Ethernet --><br>Domain Name --> Domain Name | global.iff.com  |
| Network Settings --> IPV4 --> Ethernet --><br>Primary WINS Server         | 000.000.000.000 |
| Network Settings --> IPV4 --> Ethernet --><br>Secondary WINS Server       | 000.000.000.000 |

|                                                                                                            |                      |
|------------------------------------------------------------------------------------------------------------|----------------------|
| Network Settings --> IPV4 --> Ethernet --> WINS                                                            | Deactive             |
| Network Settings --> IPV6 --> IPV6 --> IPV6                                                                | Inactive             |
| Network Settings --> SNMP --> Protocol --> IPv4                                                            | Active               |
| Network Settings --> SNMP --> SNMP --> SNMP                                                                | Active               |
| Network Settings --> SNMPv3 --> SNMP --> IPv4                                                              | Active               |
| Network Settings --> SNMPv3 --> SNMPv3 Setting --> Authentication Algorithm                                | MD5                  |
| Network Settings --> SNMPv3 --> SNMPv3 Setting --> Encryption Algorithm                                    | DES                  |
| Network Settings --> SNMPv3 --> SNMPv3 Setting --> Permit SNMPv3 Communication                             | Encryption/Cleartext |
| Network Settings --> SNMPv3 --> SNMPv3 Setting --> SNMPv3 Function                                         | Active               |
| Network Settings --> SNMPv3 --> SNMPv3 Setting --> SNMPv3 Trap Communication                               | Active               |
| Printer Settings --> Printer Basic Settings --> System --> Auto Continue                                   | On                   |
| Printer Settings --> Printer Basic Settings --> System --> Auto Continue --> Auto Continue Time            | 5                    |
| Printer Settings --> Printer Basic Settings --> System --> Auto Delete Store Print Jobs                    | On                   |
| Printer Settings --> Printer Basic Settings --> System --> Auto Delete Store Print Jobs --> Time(days)     | 1                    |
| Printer Settings --> Printer Basic Settings --> System --> Auto Delete Temporary Print Jobs                | On                   |
| Printer Settings --> Printer Basic Settings --> System --> Auto Delete Temporary Print Jobs --> Time(days) | 3                    |
| Scanner --> Send Settings --> Insert Additional Email Info --> Insert Additional Email Info                | On                   |
| Scanner --> Send Settings --> Insert Additional Email Info --> Insert Additional Email Info --> Language   | English              |
| Scanner --> Send Settings --> Max Email Size --> Set max email size                                        | On                   |

Scanner --> Send Settings --> Max Email Size  
--> Set max email size --> Max email size 35000

Security --> IEEE 802.1X --> Domain Name --> Domain Name global.iff.com

Security --> Network --> Bonjour --> IPV4 Inactive

Security --> Network --> DIPRINT --> IPV4 Active

Security --> Network --> FTP --> IPV6 Inactive

Security --> Network --> LPR --> IPV4 Active

Security --> Network --> NetBIOS over TCP/IPV4 --> IPV4 Inactive

Security --> Network --> RHPP --> IPV4 Active

Security --> Network --> RSH/RCP --> IPV4 Active

Security --> Network --> sftp --> IPV4 Inactive

Security --> Network --> SNMP --> Permit Settings by SNMPv1 and SNMPv2 On

Security --> Network --> SNMP --> SNMPv1, v2 Function Active

Security --> Network --> SNMP --> SNMPv3 Active

Security --> Network --> ssh --> IPV4 Inactive

Security --> Network --> TCP/IP --> IPV4 Active

Security --> Network --> TELNET --> IPV4 Active

Security --> Network --> WSD (Encrypted Communication of Device) --> IPV4 Active

Security --> Network --> WSD (Printer) --> IPV4 Active

Security --> Network --> WSD (Scanner) --> IPV4 Active

SOP --> PERSONAL --> Screen Device Settings --> Screen SD Card Slot Inactive

SOP --> PERSONAL --> Screen Device Settings --> Screen USB Memory Slot Inactive

User Tools --> Administrator Authentication Management --> File Administrator Authentication --> File Administrator Authentication On

User Tools --> Administrator Authentication Management --> File Administrator Authentication --> File Administrator Authentication --> Administrator Tools true

|                                                                                                                                                            |                 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| User Tools --> Administrator Authentication Management --> User Administrator Authentication --> User Administrator Authentication                         | On              |
| User Tools --> Administrator Authentication Management --> User Administrator Authentication --> User Administrator Authentication --> Administrator Tools | true            |
| User Tools --> Administrator Tools --> General Settings --> Auto erase memory setting                                                                      | On              |
| User Tools --> Administrator Tools --> General Settings --> HDD Erase Method                                                                               | DoD (5220.22-M) |
| User Tools --> File Transfer --> General Settings --> Max reception email size                                                                             | 35              |