

Configured Settings

CCD Information

Customer Name: International Flavors & Fragrances Inc.
 CCD Name: International Flavors & Fragrances Inc._2070433
 Account Number: 2070433
Model/Solution: IM350F
 CCD Type: Hardware
 CCD Number: 11529

Manual Settings

Full Path	Value	Comments
Device Settings --> Email --> Email --> Administrator Email Address	gps-device@iff.com	
Manual Configuration --> General Configuration --> Dynamic settings --> Device Certificate	Validity Period 10 years Algorithm Signature Max key length supported by device (512/1024/2048/4096)	
Manual Configuration --> General Configuration --> Dynamic settings --> SP Modes: Copy SP Modes	SP 5-966-001 set to 1	
Network Settings --> Airprint --> AirPrint --> AirPrint	Inactive	
Network Settings --> SNMPv3 --> Protocol --> SNMP	Active	
Remote --> Remote Communications --> @Remote Registration --> Registration Options	DO NOT REGISTER: SNLX with @Remote Connector/ @Remote Connector NX	
Scanner --> Default Settings for Normal Screens (Classic) on Device --> Send File Type --> Send File Type	Multi-page: PDF	
Scanner --> Default Settings for Simplified Screens (Classic) on Device --> Send File Type --> Send File Type	Multi-page: PDF	
Security --> Network --> SSDP --> IPV4	Inactive	
Security --> Network --> WSD (Device) --> IPV4	Active	
SOP --> DEVICE --> Remote Panel Operation --> Remote Panel Operation - Manual	Enabled	

SP Settings --> Copy SP Modes --> SP5 - 888
--> 888 - Personal info protect 1: Protection for logs

SP Settings --> Copy SP Modes --> SP5 - 967
- 001 --> 5-967-001 – Disable Document Server 1: OFF

SP Settings --> Printer SP Modes --> SP1-001
--> 1001-006 bit 1 - Lock Sample print 1: ON

User Tools --> Administrator Tools -->
General Settings --> Machine Data Encryption Settings/Encrypt Format All Data

User Tools --> File Transfer --> General
Settings --> Administrators email address gps-device@iff.com

User Tools --> File Transfer --> SMTP -->
SMTP Server Name smtp.global.iff.com

Automatic Settings

Full Path	Value	Comments
-----------	-------	----------

Device Settings --> Administrator Authentication Management --> File Administrator Authentication --> File Administrator Authentication	On	
--	----	--

Device Settings --> Administrator Authentication Management --> File Administrator Authentication --> File Administrator Authentication --> Administrator Tools	true	
---	------	--

Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication	On	
--	----	--

Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication --> Administrator Tools	true	
---	------	--

Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication --> File Transfer	true	
--	------	--

Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication --> General Features	true	
--	------	--

Device Settings --> Administrator
Authentication Management --> Machine
Administrator Authentication --> Machine
Administrator Authentication --> Interface

true

Device Settings --> Administrator
Authentication Management --> Machine
Administrator Authentication --> Machine
Administrator Authentication --> Maintenance

true

Device Settings --> Administrator
Authentication Management --> Machine
Administrator Authentication --> Machine
Administrator Authentication --> Timer
Settings

true

Device Settings --> Administrator
Authentication Management --> Machine
Administrator Authentication --> Machine
Administrator Authentication --> Tray Paper
Settings

true

Device Settings --> Administrator
Authentication Management --> Network
Administrator Authentication --> Network
Administrator Authentication

On

Device Settings --> Administrator
Authentication Management --> Network
Administrator Authentication --> Network
Administrator Authentication --> Administrator
Tools

true

Device Settings --> Administrator
Authentication Management --> Network
Administrator Authentication --> Network
Administrator Authentication --> File Transfer

true

Device Settings --> Administrator
Authentication Management --> Network
Administrator Authentication --> Network
Administrator Authentication --> Interface

true

Device Settings --> Administrator
Authentication Management --> User
Administrator Authentication --> User
Administrator Authentication

On

Device Settings --> Administrator
Authentication Management --> User
Administrator Authentication --> User
Administrator Authentication --> Administrator
Tools

true

Device Settings --> Email --> Email --> Auto
Specify Sender Name

On

Device Settings --> Email --> Reception -->
Max Reception Email Size

2

Device Settings --> Email --> SMTP --> SMTP
Server Name smtp.global.iff.com

Device Settings --> Program/Change
Administrator --> Administrator 1 --> Login
User Name admin

Device Settings --> Program/Change
Administrator --> Administrator 1 --> Login
User Password 20r1c0h21

Device Settings --> Program/Change
Administrator --> Administrator 2 --> Login
User Name ricoh

Device Settings --> Program/Change
Administrator --> Administrator 2 --> Login
User Password 21!ffxx1

Device Settings --> Program/Change
Administrator --> File Administrator -->
Administrator 1 true

Device Settings --> Program/Change
Administrator --> Machine Administrator -->
Administrator 1 true

Device Settings --> Program/Change
Administrator --> Network Administrator -->
Administrator 1 true

Device Settings --> Program/Change
Administrator --> User Administrator -->
Administrator 1 true

Device Settings --> Program/Change
Administrator --> User Administrator -->
Administrator 2 true

Device Settings --> System --> General
Settings --> Media Slot Use - Print from
Memory Storage Device Prohibit

Device Settings --> System --> General
Settings --> Media Slot Use - Store to Memory
Device Prohibit

Network Settings --> Bonjour --> Bonjour -->
IPV4 Inactive

Network Settings --> Community -->
Community Name 1 --> Community name 20iFF%GpS21

Network Settings --> Community -->
Community Name 1 --> IPV4 Active

Network Settings --> Community -->
Community Name 2 --> Access Type read-write

Network Settings --> Community -->
Community Name 2 --> Community name r1c0h#pCFS

Network Settings --> Community -->
Community Name 2 --> IPv4 Active

Network Settings --> IPV4 --> Details -->
DIPRINT Timeout Period 60

Network Settings --> IPV4 --> Details --> DNS
Server Specify

Network Settings --> IPV4 --> Details --> DNS
Server --> DNS Server 1 10.13.140.12

Network Settings --> IPV4 --> Details --> DNS
Server --> DNS Server 2 10.13.140.10

Network Settings --> IPV4 --> Details --> DNS
Server --> DNS Server 3 0.0.0.0

Network Settings --> IPV4 --> Details --> FTP Inactive

Network Settings --> IPV4 --> Details --> IPP Active

Network Settings --> IPV4 --> Details -->
RHPP Active

Network Settings --> IPV4 --> Details -->
RSH/RCP Active

Network Settings --> IPV4 --> Details -->
SFTP Active

Network Settings --> IPV4 --> Details --> WSD
(Device) Active

Network Settings --> IPV4 --> Details --> WSD
(Printer) Active

Network Settings --> IPV4 --> Ethernet -->
DHCP Inactive

Network Settings --> IPV4 --> Ethernet -->
Domain Name Specify

Network Settings --> IPV4 --> Ethernet -->
Domain Name --> Domain Name global.iff.com

Network Settings --> IPV4 --> Ethernet -->
Primary WINS Server 000.000.000.000

Network Settings --> IPV4 --> Ethernet -->
Secondary WINS Server 000.000.000.000

Network Settings --> IPV4 --> Ethernet -->
WINS Deactive

Network Settings --> IPV6 --> IPV6 --> IPV6 Inactive

Network Settings --> SNMP --> Protocol --> IPv4	Active
Network Settings --> SNMP --> SNMP --> SNMP	Active
Network Settings --> SNMPv3 --> SNMP --> IPv4	Active
Network Settings --> SNMPv3 --> SNMPv3 Setting --> Authentication Algorithm	MD5
Network Settings --> SNMPv3 --> SNMPv3 Setting --> Encryption Algorithm	DES
Network Settings --> SNMPv3 --> SNMPv3 Setting --> Permit SNMPv3 Communication	Encryption/Cleartext
Network Settings --> SNMPv3 --> SNMPv3 Setting --> SNMPv3 Function	Active
Network Settings --> SNMPv3 --> SNMPv3 Setting --> SNMPv3 Trap Communication	Active
Printer Settings --> Printer Basic Settings --> System --> Auto Continue	On
Printer Settings --> Printer Basic Settings --> System --> Auto Continue --> Auto Continue Time	5
Printer Settings --> Printer Basic Settings --> System --> Auto Delete Store Print Jobs	On
Printer Settings --> Printer Basic Settings --> System --> Auto Delete Store Print Jobs --> Time(days)	1
Printer Settings --> Printer Basic Settings --> System --> Auto Delete Temporary Print Jobs	On
Printer Settings --> Printer Basic Settings --> System --> Auto Delete Temporary Print Jobs --> Time(days)	3
Scanner --> Send Settings --> Insert Additional Email Info --> Insert Additional Email Info	On
Scanner --> Send Settings --> Insert Additional Email Info --> Insert Additional Email Info --> Language	English
Scanner --> Send Settings --> Max Email Size --> Set max email size	On
Scanner --> Send Settings --> Max Email Size --> Set max email size --> Max email size	35000

Security --> IEEE 802.1X --> Domain Name --> Domain Name global.iff.com

Security --> Network --> Bonjour --> IPV4 Inactive

Security --> Network --> DIPRINT --> IPV4 Active

Security --> Network --> FTP --> IPV6 Inactive

Security --> Network --> LPR --> IPV4 Active

Security --> Network --> NetBIOS over TCP/IPV4 --> IPV4 Inactive

Security --> Network --> RHPP --> IPV4 Active

Security --> Network --> RSH/RCP --> IPV4 Active

Security --> Network --> sftp --> IPV4 Inactive

Security --> Network --> SNMP --> Permit Settings by SNMPv1 and SNMPv2 On

Security --> Network --> SNMP --> SNMPv1, v2 Function Active

Security --> Network --> SNMP --> SNMPv3 Active

Security --> Network --> ssh --> IPV4 Inactive

Security --> Network --> TCP/IP --> IPV4 Active

Security --> Network --> TELNET --> IPV4 Active

Security --> Network --> WSD (Encrypted Communication of Device) --> IPV4 Active

Security --> Network --> WSD (Printer) --> IPV4 Active

Security --> Network --> WSD (Scanner) --> IPV4 Active

SOP --> PERSONAL --> Screen Device Settings --> Screen SD Card Slot Inactive

SOP --> PERSONAL --> Screen Device Settings --> Screen USB Memory Slot Inactive

User Tools --> Administrator Authentication Management --> File Administrator Authentication --> File Administrator Authentication On

User Tools --> Administrator Authentication Management --> File Administrator Authentication --> File Administrator Authentication --> Administrator Tools true

User Tools --> Administrator Authentication Management --> User Administrator Authentication --> User Administrator Authentication	On
User Tools --> Administrator Authentication Management --> User Administrator Authentication --> User Administrator Authentication --> Administrator Tools	true
User Tools --> Administrator Tools --> General Settings --> Auto erase memory setting	On
User Tools --> Administrator Tools --> General Settings --> HDD Erase Method	DoD (5220.22-M)
User Tools --> File Transfer --> General Settings --> Max reception email size	35