

Configured Settings

CCD Information

Customer Name: International Flavors & Fragrances Inc.
 CCD Name: International Flavors & Fragrances Inc._2070433
 Account Number: 2070433
Model/Solution: IMC4510
 CCD Type: Hardware
 CCD Number: 12449

Manual Settings

Full Path	Value	Comments
Device Settings --> Administrator Authentication Management --> File Administrator Authentication --> File Administrator Authentication	On	
Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication	On	
Device Settings --> Administrator Authentication Management --> Network Administrator Authentication --> Network Administrator Authentication	On	
Device Settings --> Administrator Authentication Management --> User Administrator Authentication --> User Administrator Authentication	On	
Device Settings --> Email --> Email --> Administrator Email Address	gps-device@iff.com	
Device Settings --> Email --> Email --> Administrator Email Address	gps-device@iff.com	
Device Settings --> Email --> Email --> Auto Specify Sender Name	On	
Device Settings --> Email --> Reception --> Max Reception Email Size	2	
Device Settings --> Email --> SMTP --> SMTP Server Name	smtp.global.iff.com	

Device Settings --> Program/Change Administrator --> Administrator 1 --> Login User Name admin

Device Settings --> Program/Change Administrator --> Administrator 1 --> Login User Password 20r1c0h21

Device Settings --> Program/Change Administrator --> Administrator 2 --> Login User Name ricoh

Device Settings --> Program/Change Administrator --> Administrator 2 --> Login User Password 21!ffxx1

Device Settings --> Program/Change Administrator --> File Administrator --> Administrator 1 true

Device Settings --> Program/Change Administrator --> Machine Administrator --> Administrator 1 true

Device Settings --> Program/Change Administrator --> Network Administrator --> Administrator 1 true

Device Settings --> Program/Change Administrator --> User Administrator --> Administrator 1 true

Device Settings --> Program/Change Administrator --> User Administrator --> Administrator 2 true

Device Settings --> System --> General Settings --> Media Slot Use - Print from Memory Storage Device Prohibit

Device Settings --> System --> General Settings --> Media Slot Use - Store to Memory Device Prohibit

Manual Configuration --> General Configuration --> Dynamic settings --> Device Certificate Validity Period 10 years Algorithm Signature Max key length supported by device (512/1024/2048/4096)

Manual Configuration --> General Configuration --> Dynamic settings --> Device Certificate Validity Period 10 years Algorithm Signature Max key length supported by device (512/1024/2048/4096)

Manual Configuration --> General Configuration --> Dynamic settings --> HDD enabled devices *****NOTE***** must enable encryption and DOSS - set to overwrite method DoD for all devices configured with HDD

Manual Configuration --> General Configuration --> Dynamic settings --> HDD enabled devices *****NOTE***** must enable encryption and DOSS - set to overwrite method DoD for all devices configured with HDD

Manual Configuration --> General Configuration --> Dynamic settings --> SP Modes: Copy SP Modes SP 5-966-001 set to 1

Manual Configuration --> General Configuration --> Dynamic settings --> SP Modes: Copy SP Modes SP 5-966-001 set to 1

Network Settings --> Airprint --> AirPrint --> AirPrint Inactive

Network Settings --> Airprint --> AirPrint --> AirPrint Inactive

Network Settings --> Bonjour --> Bonjour --> IPV4 Inactive

Network Settings --> Community --> Community Name 1 --> Community name 20iFF%GpS21

Network Settings --> Community --> Community Name 1 --> IPV4 Active

Network Settings --> Community --> Community Name 2 --> Access Type read-write

Network Settings --> Community --> Community Name 2 --> Community name r1c0h#pCFS

Network Settings --> Community --> Community Name 2 --> IPV4 Active

Network Settings --> IPV4 --> Details --> DIPRINT Timeout Period 60

Network Settings --> IPV4 --> Details --> DNS Server Specify

Network Settings --> IPV4 --> Details --> DNS Server --> DNS Server 1 10.13.140.12

Network Settings --> IPV4 --> Details --> DNS Server --> DNS Server 2 10.13.140.10

Network Settings --> IPV4 --> Details --> DNS Server --> DNS Server 3 0.0.0.0

Network Settings --> IPV4 --> Details --> FTP Inactive

Network Settings --> IPV4 --> Details --> IPP Active

Network Settings --> IPV4 --> Details --> RHPP Active

Network Settings --> IPV4 --> Details --> RSH/RCP	Active
Network Settings --> IPV4 --> Details --> SFTP	Active
Network Settings --> IPV4 --> Details --> WSD (Device)	Active
Network Settings --> IPV4 --> Details --> WSD (Printer)	Active
Network Settings --> IPV4 --> Ethernet --> DHCP	Inactive
Network Settings --> IPV4 --> Ethernet --> Domain Name	Specify
Network Settings --> IPV4 --> Ethernet --> Domain Name --> Domain Name	global.iff.com
Network Settings --> IPV4 --> Ethernet --> Primary WINS Server	000.000.000.000
Network Settings --> IPV4 --> Ethernet --> Secondary WINS Server	000.000.000.000
Network Settings --> IPV4 --> Ethernet --> WINS	Deactive
Network Settings --> IPV6 --> IPV6 --> IPV6	Inactive
Network Settings --> SNMP --> Protocol --> IPv4	Active
Network Settings --> SNMP --> SNMP --> SNMP	Active
Network Settings --> SNMPv3 --> Protocol --> SNMP	Active
Network Settings --> SNMPv3 --> Protocol --> SNMP	Active
Network Settings --> SNMPv3 --> SNMP --> IPv4	Active
Network Settings --> SNMPv3 --> SNMPv3 Setting --> Authentication Algorithm	MD5
Network Settings --> SNMPv3 --> SNMPv3 Setting --> Encryption Algorithm	DES
Network Settings --> SNMPv3 --> SNMPv3 Setting --> Permit SNMPv3 Communication	Encryption/Cleartext
Network Settings --> SNMPv3 --> SNMPv3 Setting --> SNMPv3 Function	Active
Network Settings --> SNMPv3 --> SNMPv3 Setting --> SNMPv3 Trap Communication	Active

Printer Settings --> Printer Basic Settings -->
System --> Auto Continue On

Printer Settings --> Printer Basic Settings -->
System --> Auto Continue --> Auto Continue
Time 5

Printer Settings --> Printer Basic Settings -->
System --> Auto Delete Store Print Jobs On

Printer Settings --> Printer Basic Settings -->
System --> Auto Delete Store Print Jobs -->
Time(days) 1

Printer Settings --> Printer Basic Settings -->
System --> Auto Delete Temporary Print Jobs On

Printer Settings --> Printer Basic Settings -->
System --> Auto Delete Temporary Print Jobs
--> Time(days) 3

Remote --> Remote Communications -->
@Remote Registration --> Registration
Options DO NOT REGISTER: SNLX with
@Remote Connector/ @Remote
Connector NX

Remote --> Remote Communications -->
@Remote Registration --> Registration
Options DO NOT REGISTER: SNLX with
@Remote Connector/ @Remote
Connector NX

Scanner --> Default Settings for Normal
Screens (Classic) on Device --> Send File
Type --> Send File Type Multi-page: PDF

Scanner --> Default Settings for Normal
Screens (Classic) on Device --> Send File
Type --> Send File Type Multi-page: PDF

Scanner --> Default Settings for Simplified
Screens (Classic) on Device --> Send File
Type --> Send File Type Multi-page: PDF

Scanner --> Default Settings for Simplified
Screens (Classic) on Device --> Send File
Type --> Send File Type Multi-page: PDF

Scanner --> Send Settings --> Insert
Additional Email Info --> Insert Additional
Email Info On

Scanner --> Send Settings --> Insert
Additional Email Info --> Insert Additional
Email Info --> Language English

Scanner --> Send Settings --> Max Email Size
--> Set max email size On

Scanner --> Send Settings --> Max Email Size
--> Set max email size --> Max email size 35000

Security --> IEEE 802.1X --> Domain Name --> Domain Name global.iff.com

Security --> Network --> Bonjour --> IPV4 Inactive

Security --> Network --> DIPRINT --> IPV4 Active

Security --> Network --> FTP --> IPV6 Inactive

Security --> Network --> LPR --> IPV4 Active

Security --> Network --> NetBIOS over TCP/IPV4 --> IPV4 Inactive

Security --> Network --> RHPP --> IPV4 Active

Security --> Network --> RSH/RCP --> IPV4 Active

Security --> Network --> sftp --> IPV4 Inactive

Security --> Network --> SNMP --> Permit Settings by SNMPv1 and SNMPv2 On

Security --> Network --> SNMP --> SNMPv1, v2 Function Active

Security --> Network --> SNMP --> SNMPv3 Active

Security --> Network --> SSDP --> IPV4 Inactive

Security --> Network --> SSDP --> IPV4 Inactive

Security --> Network --> ssh --> IPV4 Inactive

Security --> Network --> TCP/IP --> IPV4 Active

Security --> Network --> TELNET --> IPV4 Active

Security --> Network --> WSD (Device) --> IPV4 Active

Security --> Network --> WSD (Device) --> IPV4 Active

Security --> Network --> WSD (Encrypted Communication of Device) --> IPV4 Active

Security --> Network --> WSD (Printer) --> IPV4 Active

Security --> Network --> WSD (Scanner) --> IPV4 Active

SOP --> DEVICE --> Remote Panel Operation --> Remote Panel Operation - Manual Enabled

SOP --> DEVICE --> Remote Panel Operation --> Remote Panel Operation - Manual Enabled

SOP --> PERSONAL --> Screen Device Settings --> Screen SD Card Slot Inactive

SOP --> PERSONAL --> Screen Device
Settings --> Screen USB Memory Slot Inactive

SP Settings --> Copy SP Modes --> SP5 - 888
--> 888 - Personal info protect 1: Protection for logs

SP Settings --> Copy SP Modes --> SP5 - 888
--> 888 - Personal info protect 1: Protection for logs

SP Settings --> Copy SP Modes --> SP5 - 967
- 001 --> 5-967-001 – Disable Document
Server 1: OFF

SP Settings --> Copy SP Modes --> SP5 - 967
- 001 --> 5-967-001 – Disable Document
Server 1: OFF

SP Settings --> Printer SP Modes --> SP1-001
--> 1001-006 bit 1 - Lock Sample print 1: ON

SP Settings --> Printer SP Modes --> SP1-001
--> 1001-006 bit 1 - Lock Sample print 1: ON

User Tools --> Administrator Authentication
Management --> File Administrator
Authentication --> File Administrator
Authentication On

User Tools --> Administrator Authentication
Management --> User Administrator
Authentication --> User Administrator
Authentication On

User Tools --> Administrator Tools -->
General Settings --> Auto erase memory
setting On

User Tools --> Administrator Tools -->
General Settings --> HDD Erase Method DoD (5220.22-M)

User Tools --> Administrator Tools -->
General Settings --> Machine Data Encryption
Settings/Encrypt Format All Data

User Tools --> Administrator Tools -->
General Settings --> Machine Data Encryption
Settings/Encrypt Format All Data

User Tools --> File Transfer --> General
Settings --> Administrators email address gps-device@iff.com

User Tools --> File Transfer --> General
Settings --> Administrators email address gps-device@iff.com

User Tools --> File Transfer --> General
Settings --> Max reception email size 35

User Tools --> File Transfer --> SMTP -->
SMTP Server Name smtp.global.iff.com

User Tools --> File Transfer --> SMTP -->
SMTP Server Name smtp.global.iff.com

Automatic Settings

Full Path	Value	Comments
Device Settings --> Administrator Authentication Management --> File Administrator Authentication --> File Administrator Authentication	On	
Device Settings --> Administrator Authentication Management --> File Administrator Authentication --> File Administrator Authentication --> Administrator Tools	true	
Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication	On	
Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication --> Administrator Tools	true	
Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication --> File Transfer	true	
Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication --> General Features	true	
Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication --> Interface	true	
Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication --> Maintenance	true	
Device Settings --> Administrator Authentication Management --> Machine Administrator Authentication --> Machine Administrator Authentication --> Timer Settings	true	

Device Settings --> Administrator
Authentication Management --> Machine
Administrator Authentication --> Machine
Administrator Authentication --> Tray Paper
Settings

true

Device Settings --> Administrator
Authentication Management --> Network
Administrator Authentication --> Network
Administrator Authentication

On

Device Settings --> Administrator
Authentication Management --> Network
Administrator Authentication --> Network
Administrator Authentication --> Administrator
Tools

true

Device Settings --> Administrator
Authentication Management --> Network
Administrator Authentication --> Network
Administrator Authentication --> File Transfer

true

Device Settings --> Administrator
Authentication Management --> Network
Administrator Authentication --> Network
Administrator Authentication --> Interface

true

Device Settings --> Administrator
Authentication Management --> User
Administrator Authentication --> User
Administrator Authentication

On

Device Settings --> Administrator
Authentication Management --> User
Administrator Authentication --> User
Administrator Authentication --> Administrator
Tools

true

Device Settings --> Email --> Email --> Auto
Specify Sender Name

On

Device Settings --> Email --> Reception -->
Max Reception Email Size

2

Device Settings --> Email --> SMTP --> SMTP
Server Name

smtp.global.iff.com

Device Settings --> Program/Change
Administrator --> Administrator 1 --> Login
User Name

admin

Device Settings --> Program/Change
Administrator --> Administrator 1 --> Login
User Password

20r1c0h21

Device Settings --> Program/Change
Administrator --> Administrator 2 --> Login
User Name

ricoh

Device Settings --> Program/Change Administrator --> Administrator 2 --> Login User Password	21!ffxx1
Device Settings --> Program/Change Administrator --> File Administrator --> Administrator 1	true
Device Settings --> Program/Change Administrator --> Machine Administrator --> Administrator 1	true
Device Settings --> Program/Change Administrator --> Network Administrator --> Administrator 1	true
Device Settings --> Program/Change Administrator --> User Administrator --> Administrator 1	true
Device Settings --> Program/Change Administrator --> User Administrator --> Administrator 2	true
Device Settings --> System --> General Settings --> Media Slot Use - Print from Memory Storage Device	Prohibit
Device Settings --> System --> General Settings --> Media Slot Use - Store to Memory Device	Prohibit
Network Settings --> Bonjour --> Bonjour --> IPV4	Inactive
Network Settings --> Community --> Community Name 1 --> Community name	20iFF%GpS21
Network Settings --> Community --> Community Name 1 --> IPV4	Active
Network Settings --> Community --> Community Name 2 --> Access Type	read-write
Network Settings --> Community --> Community Name 2 --> Community name	r1c0h#pCFS
Network Settings --> Community --> Community Name 2 --> IPV4	Active
Network Settings --> IPV4 --> Details --> DIPRINT Timeout Period	60
Network Settings --> IPV4 --> Details --> DNS Server	Specify
Network Settings --> IPV4 --> Details --> DNS Server --> DNS Server 1	10.13.140.12

Network Settings --> IPV4 --> Details --> DNS
Server --> DNS Server 2 10.13.140.10

Network Settings --> IPV4 --> Details --> DNS
Server --> DNS Server 3 0.0.0.0

Network Settings --> IPV4 --> Details --> FTP Inactive

Network Settings --> IPV4 --> Details --> IPP Active

Network Settings --> IPV4 --> Details -->
RHPP Active

Network Settings --> IPV4 --> Details -->
RSH/RCP Active

Network Settings --> IPV4 --> Details -->
SFTP Active

Network Settings --> IPV4 --> Details --> WSD
(Device) Active

Network Settings --> IPV4 --> Details --> WSD
(Printer) Active

Network Settings --> IPV4 --> Ethernet -->
DHCP Inactive

Network Settings --> IPV4 --> Ethernet -->
Domain Name Specify

Network Settings --> IPV4 --> Ethernet -->
Domain Name --> Domain Name global.iff.com

Network Settings --> IPV4 --> Ethernet -->
Primary WINS Server 000.000.000.000

Network Settings --> IPV4 --> Ethernet -->
Secondary WINS Server 000.000.000.000

Network Settings --> IPV4 --> Ethernet -->
WINS Deactive

Network Settings --> IPV6 --> IPV6 --> IPV6 Inactive

Network Settings --> SNMP --> Protocol -->
IPv4 Active

Network Settings --> SNMP --> SNMP -->
SNMP Active

Network Settings --> SNMPv3 --> SNMP -->
IPv4 Active

Network Settings --> SNMPv3 --> SNMPv3
Setting --> Authentication Algorithm MD5

Network Settings --> SNMPv3 --> SNMPv3
Setting --> Encryption Algorithm DES

Network Settings --> SNMPv3 --> SNMPv3
Setting --> Permit SNMPv3 Communication Encryption/Cleartext

Network Settings --> SNMPv3 --> SNMPv3
Setting --> SNMPv3 Function Active

Network Settings --> SNMPv3 --> SNMPv3
Setting --> SNMPv3 Trap Communication Active

Printer Settings --> Printer Basic Settings -->
System --> Auto Continue On

Printer Settings --> Printer Basic Settings -->
System --> Auto Continue --> Auto Continue
Time 5

Printer Settings --> Printer Basic Settings -->
System --> Auto Delete Store Print Jobs On

Printer Settings --> Printer Basic Settings -->
System --> Auto Delete Store Print Jobs -->
Time(days) 1

Printer Settings --> Printer Basic Settings -->
System --> Auto Delete Temporary Print Jobs On

Printer Settings --> Printer Basic Settings -->
System --> Auto Delete Temporary Print Jobs
--> Time(days) 3

Scanner --> Send Settings --> Insert
Additional Email Info --> Insert Additional
Email Info On

Scanner --> Send Settings --> Insert
Additional Email Info --> Insert Additional
Email Info --> Language English

Scanner --> Send Settings --> Max Email Size
--> Set max email size On

Scanner --> Send Settings --> Max Email Size
--> Set max email size --> Max email size 35000

Security --> IEEE 802.1X --> Domain Name --
> Domain Name global.iff.com

Security --> Network --> Bonjour --> IPV4 Inactive

Security --> Network --> DIPRINT --> IPV4 Active

Security --> Network --> FTP --> IPV6 Inactive

Security --> Network --> LPR --> IPV4 Active

Security --> Network --> NetBIOS over
TCP/IPV4 --> IPV4 Inactive

Security --> Network --> RHPP --> IPV4 Active

Security --> Network --> RSH/RCP --> IPV4 Active

Security --> Network --> sftp --> IPV4	Inactive
Security --> Network --> SNMP --> Permit Settings by SNMPv1 and SNMPv2	On
Security --> Network --> SNMP --> SNMPv1, v2 Function	Active
Security --> Network --> SNMP --> SNMPv3	Active
Security --> Network --> ssh --> IPV4	Inactive
Security --> Network --> TCP/IP --> IPV4	Active
Security --> Network --> TELNET --> IPV4	Active
Security --> Network --> WSD (Encrypted Communication of Device) --> IPV4	Active
Security --> Network --> WSD (Printer) --> IPV4	Active
Security --> Network --> WSD (Scanner) --> IPV4	Active
SOP --> PERSONAL --> Screen Device Settings --> Screen SD Card Slot	Inactive
SOP --> PERSONAL --> Screen Device Settings --> Screen USB Memory Slot	Inactive
User Tools --> Administrator Authentication Management --> File Administrator Authentication --> File Administrator Authentication	On
User Tools --> Administrator Authentication Management --> File Administrator Authentication --> File Administrator Authentication --> Administrator Tools	true
User Tools --> Administrator Authentication Management --> User Administrator Authentication --> User Administrator Authentication	On
User Tools --> Administrator Authentication Management --> User Administrator Authentication --> User Administrator Authentication --> Administrator Tools	true
User Tools --> Administrator Tools --> General Settings --> Auto erase memory setting	On
User Tools --> Administrator Tools --> General Settings --> HDD Erase Method	DoD (5220.22-M)
User Tools --> File Transfer --> General Settings --> Max reception email size	35